

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**




FIG.1




FIG.2




FIG.3




FIG.4




FIG. 5(a)




FIG. 5(b)




FIG.6





FIG.7



DRYING METHOD
OF THE INVENTION

FIG.8




FIG. 9(a)




FIG. 9(b)




FIG. 9(c)




FIG. 9(d)




FIG. 9(e)




FIG. 9(f)




FIG. 9(g)




FIG. 9(h)




FIG. 9(i)

	STEP								
	1	2	3	4	5	6	7	8	9
LID OPENED									
LID CLOSED									
OVERFLOW RINSING									
N ₂ PURGE AT ORDINARY TEMPERATURES									
EXHAUST									
IPA CIRCULATION									
CRADLE MOVED UPWARD									
CRADLE MOVED DOWNWARD									
IPA MIST SUPPLIED									
DEIONIZED WATER DRAINED									
N ₂ PURGE AT HIGH TEMPERATURES									
	←60→	30←	120←	→10←	150←	→30←			

PROCESSING TIME(SECONDS)

FIG.10




FIG.11




FIG.12(a)






FIG.12(b)






FIG.13

WITH MIST-STRAIGHTENING VANE




FIG.14(a)

WITHOUT MIST-STRAIGHTENING VANE




FIG.14(b)




FIG.15




FIG.16




FIG.17